

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 28 mm

Item number: 7400287



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to 1.5 kN.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



- St** Steel
- FS** Strip galvanized

Master data

Item number	7400287
Type	S3 35028-2
Description 1	Underfloor duct, 2-part
Description 2	3 compartments
Manufacturer	OBO
Dimension	2000x350x28
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	503.717 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	11,244 kg CO2e / 1 Meter


Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height
28 mm

Item number: 7400287



Dimensions



Length	2,000 mm
Width	350 mm
Height	28 mm
Dimension a	120 mm
Dimension b	110 mm
Dimension h	28 mm

Technical data

Number of fixed partitions	2
Number of compartments	3 St.
Mounting system fastening type	Floor
Floor plate	yes
Application area	Screed-covered
Decouplable	no
Trunking width, min.	350 mm
Duct height, min.	28 mm
Usable cross-section	8722 mm ²
Removable cover	yes
Cross-section, draw a	2944 mm ²
Cross-section, draw b	2834 mm ²
Vertical load, large area	to 1,500 N