

# Technical data sheet

## Connection shackle, conductive, for EÜK-2

Item number: 7400988



Connection shackle for mounting screed-covered underfloor installation ducts.  
The connection shackle snaps in to the duct sidewalls.  
The electrical conductivity is ensured via the snap-in connection.



- St** Steel
- FS** Strip galvanized

### Master data

Item number	7400988
Type	VL 190-2
Description 1	Connection shackle
Description 2	conductive for EÜK-2
Manufacturer	OBO
Dimension	263x75x28,2
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	35 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,8512 kg CO2e / 1 Piece


# Technical data sheet

Connection shackle, conductive, for EÜK-2


Item number: 7400988



## Dimensions



Length	263 mm
Width	75 mm
Dimension a	190 mm



## Technical data

Version for	Strap
Floor plate	yes
Seal installation option	no
Suitable for expansion joint	yes
Trunking width, min.	190 mm
Trunking height, max.	48 mm
Duct height, min.	28 mm
With equipotential bonding	yes
Removable cover	yes